QUADRO A LED1X3250 J347 T840 OP LT80 F... (FELT COLOR CODE) • 1115716




Product:	Quadro A LED1x3250 J347 T840 OP LT80 F (felt color code)			
Order code:	1115716			
Family:	Quadro A LED			
Product group	: Acoustic luminaires			
GENERAL D	ΦΑΤΑ			
GENERAL D	Suspended acoustic LED luminaire			
	Suspended acoustic LED luminaire			
	Suspended acoustic LED luminaire Light distribution type: direct			

Instalation:	Suspended (wire and cap to be ordered separately). Cable 2.0m, 3x0.75mm2, transparent		
Environment	Indoor		
Application	office, education, retail, public place, hotel		

ELECTRICAL DATA

Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	24.8
Control gear:	ECG on/off	Integrated sensor:	None
Connection:	Cable 2.0m, 3x0.75mm2, transparent		
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	3214	System efficacy, lm/W:	130
CRI (Ra):	80+	ССТ, К:	4000
SDCM:	3	Distribution Type:	Direct
LED lifetime, h:	100000/L80B50		
TECHNICAL DATA			
Net weight, kg:	5.6	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0274		
Dimensions, mm:	620x620x68		
STANDARDS			
Operating temperature range, °C:	ta 15+35	Protection class IEC:	1
Ingress protection code:	IP40	Mechanical impact resistance:	IK05
EEC:	D	Certificates:	CE, UKCA, RoHS
Warranty:	3 years		
Technical drawing (ing)			

Technical drawing (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-11-02
NORTHCLIFFE LIGHTING, UAB
Raudondvario pl. 101, LT-47184 Kaunas, Lithuania
info@northcliffe.org
www.northcliffe.org