

QUADRO G LED1X3250 J466 T840 OP LT80 • 1115725



| Product: | Quadro G LED1x3250 J466 T840 OP LT80 |
|----------------|--------------------------------------|
| Order code: | 1115725 |
| Family: | Quadro G LED |
| Product group: | Acoustic luminaires |

GENERAL DATA

| Description: | Suspended acoustic LED luminaire | |
|--------------|--|--|
| | Light distribution type: direct | |
| | Optical system: opal polycarbanate diffuser | |
| | Housing: aluminium | |
| | Colour: white (RAL9003) | |
| Instalation: | Suspended (wire and cap to be ordered separately). Cable 2.0m, | |
| | 3x0.75mm2, transparent | |
| Environment | Indoor | |
| Application | office, education, retail, public place, hotel | |

ELECTRICAL DATA

| Mains voltage: | 220-240V, 0/50/60Hz | System power*, W: | 24.8 |
|----------------|---------------------------------------|--------------------|------|
| Control gear: | ECG on/off | Integrated sensor: | None |
| Connection: | Cable 2.0m, 3x0.75mm2, transparent | | |

LIGHTING DATA

| Light source and cap, W: | LED | Light source included: | yes |
|------------------------------------|---------------|------------------------|--------|
| Luminaire output*, lm(ta+25°C): | 3214 | System efficacy, lm/W: | 130 |
| CRI (Ra): | 80+ | CCT, K: | 4000 |
| SDCM: | 3 | Distribution Type: | Direct |
| LED lifetime, h: | 100000/L80B50 | | |


TECHNICAL DATA

| Net weight, kg: | 5.6 | Quantity in package, pcs: | 1 |
|---------------------------|------------|---------------------------|---|
| Packaging volume, m3/pcs: | 0.0274 | | |
| Dimensions, mm: | 620x620x68 | | |

STANDARDS

| Operating temperature range, °C: | ta 15+35 | Protection class IEC: | 1 |
|----------------------------------|----------|-------------------------------|----------------|
| Ingress protection code: | IP40 | Mechanical impact resistance: | IK05 |
| EEC: | D | Certificates: | CE, UKCA, RoHS |
| Warranty: | 3 years | | |

Technical drawing (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2023-11-02 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org