


FORMA C LED

Surface and Suspended Luminaires



Description: A decorative and modern "C" shaped LED luminaire in three sizes to fit wide range of applications
 Light distribution: direct
 Optical system: opal PMMA diffuser, UV stabilized
 Housing: steel
 Colour: white RAL 9003S

General data: Mains voltage: 220-240V, 0/50-60Hz
 LED lifetime, h: 100000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP40
 Mechanical impact resistance: IK02
 Operating temperature range, °C: ta 0...+35

Installation: Surface luminaire is designed to be fixed to ceiling of any type or suspended. Multiple wire suspension, cable cap and decorative cable accessories are available on request. Push-in terminal, 3x2x2.5mm²

Environment: Indoor

Application: Office, education, retail, public place


Product	Length, mm	Width, mm	Height, mm	Luminaire output, lm	System power, W	System efficacy, lm/W	CRI *	CCT*, K	Weight, kg
Forma C LED1x1050 J475 T830 OP LT80	600	300	80	962	8,9	108	80+	3000	2,6
Forma C LED1x1400 J476 T830 OP LT80	600	300	80	1311	12,8	102	80+	3000	2,6
Forma C LED1x1900 J477 T830 OP LT80	600	300	80	1802	18,6	97	80+	3000	2,6
Forma C LED1x1650 J478 T830 OP LT80	900	450	80	1574	14,0	112	80+	3000	3,7
Forma C LED1x2250 J479 T830 OP LT80	900	450	80	2145	20,4	105	80+	3000	3,7
Forma C LED1x3100 J480 T830 OP LT80	900	450	80	2948	30,0	98	80+	3000	3,7
Forma C LED1x2200 J481 T830 OP LT80	1200	600	80	2098	18,4	114	80+	3000	4,7
Forma C LED1x3000 J482 T830 OP LT80	1200	600	80	2859	26,0	110	80+	3000	4,7
Forma C LED1x4150 J483 T830 OP LT80	1200	600	80	3931	37,8	104	80+	3000	4,7
Forma C LED1x1050 J475 T840 OP LT80	600	300	80	1007	8,9	113	80+	4000	2,6
Forma C LED1x1400 J476 T840 OP LT80	600	300	80	1372	12,8	107	80+	4000	2,6
Forma C LED1x1900 J477 T840 OP LT80	600	300	80	1886	18,6	101	80+	4000	2,6
Forma C LED1x1650 J478 T840 OP LT80	900	450	80	1648	14,0	118	80+	4000	3,7
Forma C LED1x2250 J479 T840 OP LT80	900	450	80	2245	20,4	110	80+	4000	3,7
Forma C LED1x3100 J480 T840 OP LT80	900	450	80	3086	30,0	103	80+	4000	3,7
Forma C LED1x2200 J481 T840 OP LT80	1200	600	80	2197	18,4	119	80+	4000	4,7
Forma C LED1x3000 J482 T840 OP LT80	1200	600	80	2994	26,0	115	80+	4000	4,7
Forma C LED1x4150 J483 T840 OP LT80	1200	600	80	4115	37,8	109	80+	4000	4,7

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+
- DPRZ LT80 De-glaring micro-prismatic diffuser, matt
- DALI Driver with DALI interface and switch-control dimming
- BLT Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)
- COR Driver with Corridor function (never off)
- COR1min Driver with Corridor function 1min (switch off after 1 min.)
- COR30min Driver with Corridor function 30min (switch off after 30 min.)
- CBF2-2.0m clear Cable 2x0.75mm² for suspended luminaire up to 2.0 meters, transparent
- CBF2-3.0m clear Cable 2x0.75mm² for suspended luminaire up to 3.0 meters, transparent
- CBF3-2.0m clear Cable 3x0.75mm² for suspended luminaire up to 2.0 meters, transparent
- CBF3-3.0m clear Cable 3x0.75mm² for suspended luminaire up to 3.0 meters, transparent
- CBF5-2.0m clear Cable 5x0.75mm² for suspended luminaire up to 2.0 meters, transparent
- CBF5-3.0m clear Cable 5x0.75mm² for suspended luminaire up to 3.0 meters, transparent
- RAL RAL colour

OP LT80



Available accessories:



Product: Suspension MTG KIT SUSI
Description: Suspension wire set "I" type, 1.5m adjustable, 1pcs
**note - at least 3pcs MTG KIT SUSI for one fitting required. For exact quantity please refer to installation manual*



Product: CAP cable 3x0.75 2.0m, clear
Description: Cable 3x0.75mm² for suspended luminaire up to 2.0 meters, transparent



Product: CAP cable clip D6.3mm SET clear
Description: Cable and suspension wire clip set, 4pcs.
For cable diameter up to 6,3mm and wire diameter 1mm



Product: CAP4, light grey/ white/ black
Description: Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 3x1x1.5mm², light grey/ white/ black



Product: CAP5, light grey/ white/ black
Description: Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 5x1x1.5mm², light grey/ white/ black