


CARINA P LED

Diffuser and Wall Luminaires



Images for the product family and options:



Description:

Surface mounted LED luminaire
 Light distribution type: direct
 Optical system: translucent micro-linear polycarbonate diffuser
 Housing: steel
 Colour: white (RAL 9003)

General data:

Mains voltage: 220-240V, 0/50/60Hz
 LED lifetime, h: 100000/L80B50
 SDCM: 3
 Protection class IEC: I (II optional)
 Ingress protection code: IP54
 Mechanical impact resistance: IK05
 Protection symbol: D
 Glow wire test, °C: 850
 Operating temperature range, °C: ta -15...+35 (from 0 °C with EM3)

Installation:

On ceiling or wall. Push-in terminal, 5x2x2.5mm²

Environment:

Indoor

Application:

Office, education, hotel, corridor, staircase, healthcare, bathroom, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Carina P LED1x1500 G444 T830 MPRZ	615	97	72	1399	10,3	136	80+	3000	1,5
Carina P LED1x2050 G445 T830 MPRZ	615	97	72	1913	13,9	138	80+	3000	1,5
Carina P LED1x2700 G446 T830 MPRZ	615	97	72	2538	18,9	134	80+	3000	1,5
Carina P LED1x3050 G447 T830 MPRZ	615	97	72	2875	20,5	140	80+	3000	1,5
Carina P LED1x2750 G448 T830 MPRZ	1175	97	72	2551	18,3	140	80+	3000	2,3
Carina P LED1x3550 G449 T830 MPRZ	1175	97	72	3327	22,9	146	80+	3000	2,3
Carina P LED1x4600 G450 T830 MPRZ	1175	97	72	4336	30,5	142	80+	3000	2,3
Carina P LED1x5400 G451 T830 MPRZ	1175	97	72	5076	35,2	144	80+	3000	2,3
Carina P LED1x6100 G452 T830 MPRZ	1175	97	72	5751	39,2	147	80+	3000	2,3
Carina P LED1x3400 G453 T830 MPRZ	1455	97	72	3189	22,3	143	80+	3000	2,8
Carina P LED1x4400 G454 T830 MPRZ	1455	97	72	4159	28,6	146	80+	3000	2,8
Carina P LED1x5750 G455 T830 MPRZ	1455	97	72	5419	38,1	142	80+	3000	2,8
Carina P LED1x6700 G456 T830 MPRZ	1455	97	72	6345	42,6	149	80+	3000	2,8
Carina P LED1x7600 G457 T830 MPRZ	1455	97	72	7189	48,4	148	80+	3000	2,8
Carina P LED1x1500 G444 T840 MPRZ	615	97	72	1475	10,3	144	80+	4000	1,5
Carina P LED1x2050 G445 T840 MPRZ	615	97	72	2017	13,9	145	80+	4000	1,5
Carina P LED1x2700 G446 T840 MPRZ	615	97	72	2675	18,9	142	80+	4000	1,5
Carina P LED1x3050 G447 T840 MPRZ	615	97	72	3031	20,5	148	80+	4000	1,5
Carina P LED1x2750 G448 T840 MPRZ	1175	97	72	2689	18,3	147	80+	4000	2,3
Carina P LED1x3550 G449 T840 MPRZ	1175	97	72	3507	22,9	153	80+	4000	2,3
Carina P LED1x4600 G450 T840 MPRZ	1175	97	72	4570	30,5	150	80+	4000	2,3
Carina P LED1x5400 G451 T840 MPRZ	1175	97	72	5351	35,2	152	80+	4000	2,3
Carina P LED1x6100 G452 T840 MPRZ	1175	97	72	6062	39,2	155	80+	4000	2,3
Carina P LED1x3400 G453 T840 MPRZ	1455	97	72	3362	22,3	151	80+	4000	2,8
Carina P LED1x4400 G454 T840 MPRZ	1455	97	72	4383	28,6	153	80+	4000	2,8
Carina P LED1x5750 G455 T840 MPRZ	1455	97	72	5713	38,1	150	80+	4000	2,8
Carina P LED1x6700 G456 T840 MPRZ	1455	97	72	6688	42,6	157	80+	4000	2,8
Carina P LED1x7600 G457 T840 MPRZ	1455	97	72	7577	48,4	156	80+	4000	2,8

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

