


# CETUS P LED

## Diffuser and Wall Luminaires



**Description:** Surface mounted plastic LED luminaire  
 Light distribution type: direct  
 Optical system: opal polycarbonate diffuser, impact resistant  
 Housing: polycarbonate  
 Colour: white

**General data:** Mains voltage: 220-240V, 50/60Hz  
 LED lifetime, h: 40000/L70B50  
 SDCM: 5  
 Protection class IEC: II  
 Ingress protection code: IP65  
 Mechanical impact resistance: IK08  
 Operating temperature range, °C: ta -15...+35

**Installation:** On the ceiling or wall. Screw terminal, 2x1.5mm<sup>2</sup>

**Environment:** Indoor

**Application:** Office, education, corridor, staircase, healthcare, bathroom, public place

| Product                        | Length, mm | Width, mm | Height, mm | Luminaire output*, lm | System power*, W | System efficacy*, lm/W | CRI | CCT*, K | Weight, kg |
|--------------------------------|------------|-----------|------------|-----------------------|------------------|------------------------|-----|---------|------------|
| Cetus P LED1x1200 D671 T830 OP | 160        | 160       | 63         | 1080                  | 12               | 90                     | 80+ | 3000    | 0,19       |

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**Available options:**  
 T830 Colour temperature 3000K, CRI 80+  
 OP Opal diffuser

