


MIRA LED

Diffuser and Wall Luminaires



Description: A surface mounted mirror LED luminaire
Light distribution type: direct
Optical system: opal polycarbonate diffuser
Housing: aluminium
Colour: white

General data: Mains voltage: 220-240V, 50-60Hz
LED lifetime, h: 30000/L70B50
SDCM: 5
Protection class IEC: II (I with built-in socket)
Ingress protection code: IP44
Mechanical impact resistance: IK04
Operating temperature range, °C: ta 0...+35

Installation: On the wall (mounting brackets included). Screw terminal, 2x1.5mm² (3x1.5mm² with built-in socket)

Environment: Indoor

Application: Hotel, bathroom, healthcare



A built-in Schuko type socket outlet with hinged IP44 cover is available as an option (SOCS44). For more information see the option list.



Supplied with a wall mounting kit for easy installation. A switch on/off button is installed at the end of the body.

| Product | Length, mm | Width, mm | Height, mm | Luminaire output*, lm | System power*, W | System efficacy*, lm/W | CRI | CCT*, K | Weight, kg |
|------------------------------------|------------|-----------|------------|-----------------------|------------------|------------------------|-----|---------|------------|
| Mira LED1x1400 D552 T830 OP | 600 | 53 | 65 | 1400 | 15,0 | 93 | 80+ | 3000 | 0,54 |
| Mira LED1x1400 D553 T830 OP SOCS44 | 682 | 53 | 65 | 1400 | 15,0 | 93 | 80+ | 3000 | 0,71 |

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

SOC544 Built-in schuko socket outlet with hinged cover (IP44)
T830 Colour temperature 3000K, CRI 80+

