


PUPIS P LED

Diffuser and Wall Luminaires



Images for the product family and options:



Description: Surface mounted plastic LED luminaire
Light distribution type: direct
Optical system: opal polycarbonate diffuser, impact resistant
Housing: polycarbonate
Colour: white

General data: Mains voltage: 220-240V, 50/60Hz
LED lifetime, h: 40000/L70B50
SDCM: 5
Protection class IEC: II
Ingress protection code: IP65
Mechanical impact resistance: IK08
Operating temperature range, °C: ta -15...+35

Installation: On the ceiling or walls. Screw terminal, 2x1.5mm²

Environment: Indoor

Application: Office, education, household, corridor, staircase, healthcare, bathroom, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Pupis P LED1x500 D541 T730 OP	171	71	45	500	5,0	100	70+	3000	0,18

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- OP Opal diffuser
- T730 Colour temperature 3000K, CRI 70+

