


# BARAT

## Slim Batten Luminaire

### Waterproof and Cleanroom Luminaires



**Description:** Surface mounted waterproof luminaire for LED tubes  
 Light distribution type: direct  
 Optical system: opal polycarbonate diffuser, UV stable  
 Housing: polycarbonate  
 Colour: light grey

**General data:** Light source: LED / LEDS / LEDD  
 Mains voltage: 220-240V, 50/60Hz  
 SDCM: 3  
 Protection class IEC: I  
 Ingress protection code: IP66  
 Mechanical impact resistance: IK06  
 Protection symbol: D  
 Operating temperature range, °C: ta -20...+40

**Installation:** On the ceiling or wall (mounting brackets included), or suspended (hooks included). Push-in terminal, 3x2x2.5mm2

**Environment:** Indoor

**Application:** Industry, warehouse, hall, sports, public place, parking area, transport terminal, parking area

Product	Length, mm	Width, mm	Height, mm	Light source (W) and holder	Weight, kg
Barat 118 I14 LED ABS/PMMA	662	96	111	1xT8 LED (G13)	0,80
Barat 218 I15 LED ABS/PMMA	662	146	111	2xT8 LED (G13)	1,10
Barat 136 I16 LED ABS/PMMA	1272	96	111	1xT8 LED (G13)	1,60
Barat 236 I17 LED ABS/PMMA	1272	146	111	2xT8 LED (G13)	2,10
Barat 158 I18 LED ABS/PMMA	1572	96	111	1xT8 LED (G13)	1,90
Barat 258 I19 LED ABS/PMMA	1572	146	111	2xT8 LED (G13)	2,50
<i>Check wiring diagram before placing order: LED, LEDS, LEDD</i>					
Barat 118 I14 LED ABS/PMMA IC	662	96	111	1xT8 LED (G13)	0,80
Barat 218 I15 LED ABS/PMMA IC	662	146	111	2xT8 LED (G13)	1,10
Barat 136 I16 LED ABS/PMMA IC	1272	96	111	1xT8 LED (G13)	1,60
Barat 236 I17 LED ABS/PMMA IC	1272	146	111	2xT8 LED (G13)	2,10
Barat 158 I18 LED ABS/PMMA IC	1572	96	111	1xT8 LED (G13)	1,90
Barat 258 I19 LED ABS/PMMA IC	1572	146	111	2xT8 LED (G13)	2,50
<i>Check wiring diagram before placing order: LED, LEDS, LEDD</i>					
Barat 118 I14 LED ABS/PC	662	96	111	1xT8 LED (G13)	0,80
Barat 218 I15 LED ABS/PC	662	146	111	2xT8 LED (G13)	1,10
Barat 136 I16 LED ABS/PC	1272	96	111	1xT8 LED (G13)	1,60
Barat 236 I17 LED ABS/PC	1272	146	111	2xT8 LED (G13)	2,10
Barat 158 I18 LED ABS/PC	1572	96	111	1xT8 LED (G13)	1,90
Barat 258 I19 LED ABS/PC	1572	146	111	2xT8 LED (G13)	2,50
<i>Check wiring diagram before placing order: LED, LEDS, LEDD</i>					

**TECHNICAL DATA SHEET**

Barat 118 I14 LED ABS/PC IC	662	96	111	1xT8 LED (G13)	0,80
Barat 218 I15 LED ABS/PC IC	662	146	111	2xT8 LED (G13)	1,10
Barat 136 I16 LED ABS/PC IC	1272	96	111	1xT8 LED (G13)	1,60
Barat 236 I17 LED ABS/PC IC	1272	146	111	2xT8 LED (G13)	2,10
Barat 158 I18 LED ABS/PC IC	1572	96	111	1xT8 LED (G13)	1,90
Barat 258 I19 LED ABS/PC IC	1572	146	111	2xT8 LED (G13)	2,50

Check wiring diagram before placing order: LED, LEDS, LEDD

\* note - Check wiring diagram before placing order: LED, LEDS, LEDD

\* Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification