


# CUJAM LED

## Waterproof and Cleanroom Luminaires



<b>Description:</b>	Surface mounted waterproof low-cost LED luminaire Light distribution type: direct Optical system: opal polycarbonate diffuser Housing: polycarbonate Colour: white
<b>General data:</b>	Mains voltage: 220-240V, 50/60Hz LED lifetime, h: 25000/L70B50 SDCM: 5 Protection class IEC: II Ingress protection code: IP65 Mechanical impact resistance: IK07 Operating temperature range, °C: ta -20...+40
<b>Installation:</b>	On the ceiling or wall (mounting brackets included), or suspended. Cable, 0.25m, 2x0.75mm <sup>2</sup>
<b>Environment:</b>	Indoor
<b>Application:</b>	Industry, warehouse, public place, parking area

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Cujam LED1x3600 D595 T740 OP	1200	60	35	3600	36,0	100	70+	4000	0,40
Cujam LED1x4800 D596 T740 OP	1500	60	35	4800	48,0	100	70+	4000	0,50

\* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification  
\*note - luminaire is not suitable for frequent switching

**Available options:**

- OP Opal diffuser
- T740 Colour temperature 4000K, CRI 70+

