


NAVI P LED

Waterproof and Cleanroom Luminaires




Description:	Recessed mounted LED panel Light distribution type: direct Optical system: opal diffuser Housing: aluminum Colour: white (RAL9016)
General data:	Mains voltage: 220-240V, 50/60Hz LED lifetime, h: 50000/L70B50 SDCM: 5 Protection class IEC: II Ingress protection code: IP54 Mechanical impact resistance: IK02 Operating temperature range, °C: ta 0...+35
Installation:	In modular suspended ceilings (600), in ceilings with cut-out openings (accessories to be ordered separately). Push-in terminal, 2x2x2.5mm2
Environment:	Indoor
Application:	Healthcare, laboratory, industry

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy, lm/W	CRI	CCT, K	Weight, kg
Navi P LED1x3650 G616 T830 OP	595	595	33	3600	36,0	100	80+	3000	2,50
Navi P LED1x3650 G617 T830 OP	1195	295	33	3600	36,0	100	80+	3000	2,50
Navi P LED1x3650 G616 T840 OP	595	595	33	3650	36,0	101	80+	4000	2,50
Navi P LED1x3650 G617 T840 OP	1195	295	33	3650	36,0	101	80+	4000	2,50

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

DALI	Driver with DALI interface and switch-control dimming	EM3D	Emergency version 3 hours with DALI interface
EM3	Emergency version 3 hours	T830	Colour temperature 3000K, CRI 80+
EM3B	Emergency version 3 hours (best available technology)	T840	Colour temperature 4000K, CRI 80+
EM3A	*note - EM3B, EM3A, EM3D option not applicable with surface accessories Emergency version equipped with an autonomous testing system, 3 hours		




TECHNICAL DATA SHEET

Available accessories:



Product: Recessed MTG FRAME S626x626 RAL9003
Description: Frame for LED luminaire 595x595mm installation into plasterboard ceiling (1pcs), white steel
Product: Recessed MTG FRAME S326x1226 RAL9003
Description: Frame for LED luminaire 1195x295mm installation into plasterboard ceiling (1pcs), white steel



Product: Decorative REFLECTOR 595x595 Levanto PLN/UGR LED RAL9003
Description: Decorative reflector for LED panel 595x595mm (1pcs), white steel



Product: Decorative COVER 595x595/D500 Levanto PLN/UGR LED RAL9003
Description: Decorative cover with 500mm round opening for LED panel 595x595mm (1pcs), white steel

Applications:

