



Ain C LED

Downlights



Images for the product family and options:



Description:

Recessed mounted LED downlight
 Light distribution type: direct
 Optical system: lens, 40°
 Housing: die cast aluminium
 Colour: white, RAL 9003), black, RAL 9005
 Fire rated 30, 60 and 90 mins

General data:

Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 40000/L70B50
 SDCM: 6
 Protection class IEC: II
 Ingress protection code: IP65
 Mechanical impact resistance: IK04
 Operating temperature range, °C: ta -10...+40

Installation:

In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1mm2
 Cut out dimensions: Ø69mm

Environment:

Indoor

Application:

Office, education, household, hotel, corridor, bathroom, showroom, exhibition, public place

| Product | Length, mm | Width, mm | Height, mm | Luminaire output*, lm | System power*, W | System efficacy*, lm/W | CRI* (Ra) | CCT*, K | Weight, kg |
|--------------------------|------------|-----------|------------|-----------------------|------------------|------------------------|-----------|---------|------------|
| Ain C LED1x700 G681 T830 | 84 | 84 | 53 | 800 | 8,5 | 94 | 80+ | 3000 | 0,3 |

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- T830 Colour temperature 3000K, CRI 80+
- DALI Driver with DALI interface and switch-control dimming
- TDIM Driver with trailing-edge and leading-edge dimming
- RAL RAL colour

*note - price for uncommon RAL colour could be different from indicated. Ask before placing an order

