


ANDROMEDA P LED

Downlights



Images for the product family and options:



Description: Recessed mounted low-cost LED downlight
 Light distribution type: direct
 Optical system: opal polycarbonate diffuser
 Housing: polycarbonate
 Colour: white

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 40000/L70B50
 SDCM: 5
 Protection class IEC: II
 Ingress protection code: IP44
 Mechanical impact resistance: IK04
 Operating temperature range, °C: ta 0...+35

Installation: In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm2

Environment: Indoor

Application: Office, education, hotel, corridor, bathroom, retail, showroom, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Andromeda P LED1x700 D522 T830 OP	92	92	64	660	7	94	80+	3000	0,11
Andromeda P LED1x1000 D523 T830 OP	113	113	73	930	10	93	80+	3000	0,16
Andromeda P LED1x1400 D524 T830 OP	174	174	79	1330	14	95	80+	3000	0,28
Andromeda P LED1x2100 D525 T830 OP	244	244	95	1960	20	98	80+	3000	0,53
Andromeda P LED1x700 D522 T840 OP	92	92	64	700	7	100	80+	4000	0,11
Andromeda P LED1x1000 D523 T840 OP	113	113	73	980	10	98	80+	4000	0,16
Andromeda P LED1x1400 D524 T840 OP	174	174	79	1400	14	100	80+	4000	0,28
Andromeda P LED1x2100 D525 T840 OP	244	244	95	2060	20	103	80+	4000	0,53

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

T830 Colour temperature 3000K, CRI 80+
 T840 Colour temperature 4000K, CRI 80+
 OP Opal diffuser

STANDARD

