


ANTLIA C LED

Downlights




Description:	Surface mounted LED downlight Light distribution type: direct Optical system: opal polycarbonate diffuser Housing: aluminium Colour: white (RAL9016)
General data:	Mains voltage: 220-240V, 50-60Hz LED lifetime, h: 50000/L80B50 (75000/L80B50 low power versions) SDCM: 3 Protection class IEC: I Ingress protection code: IP44 Mechanical impact resistance: IK04 Operating temperature range, °C: ta 0...+35
Installation:	On the ceiling. Push-in terminal, 3x2x2.5mm2
Environment:	Indoor
Application:	Office, education, hotel, corridor, bathroom, retail, showroom, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Antlia C LED1x1400 D345 T830 OP	200	200	130	1261	11,8	107	80+	3000	1,00
Antlia C LED1x1900 D346 T830 OP	200	200	130	1774	16,0	111	80+	3000	1,00
Antlia C LED1x2600 D347 T830 OP	200	200	130	2458	23,1	107	80+	3000	1,00
Antlia C LED1x1400 D345 T840 OP	200	200	130	1321	11,8	112	80+	4000	1,00
Antlia C LED1x1900 D346 T840 OP	200	200	130	1858	16,0	116	80+	4000	1,00
Antlia C LED1x2600 D347 T840 OP 1G	200	200	130	2575	23,1	112	80+	4000	1,00

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- DALI Driver with DALI interface and switch-control dimming
- EM3 Emergency version 3 hours
- EM3B Emergency version 3 hours (best available technology)
- *note – EM3B options not applicable for models: D347*
- 1G Strain relief for power supply cable
- SUS Suspended version
- RAL RAL colour
- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+



Available accessories:



Product: Suspension MTG KIT Bootes C LED / Lodos S LED, white/ grey/ black
Description: Suspension wire set with cap 3x"1" type, 1.5m adjustable, 1pcs