



### ANTLIA LED

#### Downlights



<b>Description:</b>	Surface mounted LED downlight Light distribution type: direct Optical system: faceted aluminium reflector, 40°, low glare Housing: aluminum Colour: white (RAL9016)
<b>General data:</b>	Mains voltage: 220-240V, 50/60Hz LED lifetime, h: 50000/L80B50 (75000/L80B50 low power versions) SDCM: 3 Protection class IEC: I Ingress protection code: IP20 Mechanical impact resistance: IK02 Operating temperature range, °C: ta 0...+35
<b>Installation:</b>	On the ceiling. Push-in terminal, 3x2x2.5mm <sup>2</sup>
<b>Environment:</b>	Indoor
<b>Application:</b>	Office, education, hotel, corridor, bathroom, retail, showroom, exhibition, public place


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Antlia LED1x1800 D342 T830	168	168	172	1715	13,5	127	80+	3000	1
Antlia LED1x2400 D343 T830	168	168	172	2330	19,8	118	80+	3000	1
Antlia LED1x3200 D344 T830	168	168	172	3137	26,8	117	80+	3000	1
Antlia LED1x1800 D342 T840	168	168	172	1813	13,5	134	80+	4000	1
Antlia LED1x2400 D343 T840	168	168	172	2463	19,8	124	80+	4000	1
Antlia LED1x3200 D344 T840	168	168	172	3316	26,8	124	80+	4000	1

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

#### Available options:

T830	Colour temperature 3000K, CRI 80+	T940 NATURAL	Colour temperature 4000K, CRI 95+ NATURAL
T840	Colour temperature 4000K, CRI 80+	DALI	Driver with DALI interface and switch-control dimming
T927 NATURAL	Colour temperature 2700K, CRI 95+ NATURAL	SUS	Suspended version
T930 NATURAL	Colour temperature 3000K, CRI 95+ NATURAL	RAL	RAL colour

#### STANDARD



#### Available accessories:



Product: Suspension MTG KIT SUSI  
Description: Suspension wire set "I" type, 1.5m adjustable, 1pcs  
\*note - 1pcs MTG KIT SUSI for one fitting required