


AURIGA P LED

Downlights



Images for the product family and options:



Description: Recessed mounted LED downlight
 Light distribution type: direct
 Optical system: faceted aluminium reflector, 60°/ matt aluminium reflector, 80°, low glare, opal PMMA diffuser
 Housing: aluminium
 Colour: white, RAL9016

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 74000/L80B50
 SDCM: 6
 Protection class IEC: II
 Ingress protection code: IP44
 Mechanical impact resistance: IK04
 Operating temperature range, °C: ta 0...+35

Installation: In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm2

Environment: Indoor

Application: Office, education, hotel, corridor, bathroom, retail, showroom, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Auriga P LED1x1900 G986 T840 R60	174	174	87	1900	20	95	80+	4000	0,4
Auriga P LED1x2550 G987 T840 R60	232	232	110	2520	28	90	80+	4000	0,7
Auriga P LED1x950 J721 T840 R60	114	114	66	950	10	95	80+	4000	0,3
Auriga P LED1x3350 J722 T840 R60	232	232	110	3325	35	95	80+	4000	0,7
Auriga P LED1x2400 G986 T840 R80	174	174	87	2400	20	120	80+	4000	0,4
Auriga P LED1x3350 G987 T840 R80	232	232	110	3320	28	119	80+	4000	0,7
Auriga P LED1x1100 J723 T840 R80	114	114	66	1100	10	110	80+	4000	0,3
Auriga P LED1x4050 J724 T840 R80	232	232	110	4025	35	115	80+	4000	0,7

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+
- T857 Colour temperature 5700K, CRI 80+
- DALI Driver with DALI interface and switch-control dimming
- EM3 Emergency version 3 hours
- EM3B Emergency version 3 hours (best available technology)
- EM3A Emergency version equipped with an autonomous testing system, 3 hours
- EM3D Emergency version 3 hours with DALI interface
- WIE3-0.5m 3-pole "Wieland - gesis classic" type or compatible connector with 0.5m cable

- WIE5D-0.5m 5-pole DALI "Wieland - gesis classic" type or compatible connector with 0.5m cable
- QBX3-0.1m 3-pole quick connection box on 0.1m cable, Push-in terminal, 3x2x2.5mm2
- Europlug-1.5m 2-pole "Europlug" type plug with 2x1.0mm² 1.5m cable
- Europlug-3.0m 2-pole "Europlug" type plug with 2x1.0mm² 3.0m cable
- RND BLACK Round luminaire frame in black
- SQ WHITE Square luminaire frame in white
- SQ BLACK Square luminaire frame in black
- GLASS WHITE Round luminaire frame in white, with dropped down glass cover
- GLASS BLACK Round luminaire frame in black, with dropped down glass cover

