


# CRATER

## Downlights



**Images for the product family and options:**



**Description:** Recessed mounted LED spotlight  
Light distribution type: direct  
Optical system: white aluminium reflector, symmetrical/ asymmetrical  
Housing: aluminium  
Colour: white (RAL 9016)

**General data:** Mains voltage: 220-240V, 50/60Hz  
Protection class IEC: I  
Ingress protection code: IP20  
Mechanical impact resistance: IK04  
Operating temperature range, °C: ta 0...+35

**Installation:** In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 3x2x2.5mm2

**Environment:** Indoor

**Application:** Office, education, hotel, corridor, showroom, exhibition, public place



Suitable for use with GU10 LED bulbs. Bulbs are ordered separately


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Crater 1GU10 U01	83	83	110						0,13
Crater 1GU10 U01 ANGLE	83	83	110						0,13

\* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**Available options:**

L30 Optics with 30° beam angle T840 Colour temperature 4000K, CRI 80+  
T830 Colour temperature 3000K, CRI 80+

**STANDARD**



**ANGLE**

