


TETRA A LED

Downlights



Description:	Recessed mounted LED downlight Light distribution type: direct Optical system: translucent micro-prismatic PMMA diffuser Housing: steel Colour: white (RAL 9003)
General data:	Mains voltage: 220-240V, 0/50-60Hz LED lifetime, h: 50000/L80B50 (75000/L80B50 low power versions) SDCM: 3 Protection class IEC: II Ingress protection code: IP44 Mechanical impact resistance: IK05 Operating temperature range, °C: ta 0...+35
Installation:	In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm ²
Environment:	Indoor
Application:	Office, education, hotel, corridor, bathroom, retail, showroom, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Tetra A LED1x1200 D984 T830 MPRZ LT92	260	260	65	1107	10,2	109	80+	3000	1,5
Tetra A LED1x1650 D985 T830 MPRZ LT92	260	260	65	1547	14,7	105	80+	3000	1,5
Tetra A LED1x2200 D986 T830 MPRZ LT92	260	260	65	2084	20,1	104	80+	3000	1,5
Tetra A LED1x2700 D987 T830 MPRZ LT92	260	260	65	2550	27,6	92	80+	3000	1,5
Tetra A LED1x1200 D984 T840 MPRZ LT92	260	260	65	1167	10,2	114	80+	4000	1,5
Tetra A LED1x1650 D985 T840 MPRZ LT92	260	260	65	1631	14,7	111	80+	4000	1,5
Tetra A LED1x2200 D986 T840 MPRZ LT92	260	260	65	2197	20,1	109	80+	4000	1,5
Tetra A LED1x2700 D987 T840 MPRZ LT92	260	260	65	2688	27,6	97	80+	4000	1,5


*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

T830	Colour temperature 3000K, CRI 80+	WIE5D-0.5m	5-pole DALI "Wieland - gesis classic" type or compatible connector with 0.5m cable
T840	Colour temperature 4000K, CRI 80+	QBX3-0.1m	3-pole quick connection box on 0.1m cable, Push-in terminal, 3x2x2.5mm ²
DALI	Driver with DALI interface and switch-control dimming	Europlug-1.5m	2-pole "Europlug" type plug with 2x1.0mm ² 1.5m cable
EM3	Emergency version 3 hours	Europlug-3.0m	2-pole "Europlug" type plug with 2x1.0mm ² 3.0m cable
EM3B	Emergency version 3 hours (best available technology)	RAL	RAL colour
EM3A	Emergency version equipped with an autonomous testing system, 3 hours		
EM3D	Emergency version 3 hours with DALI interface		
WIE3-0.5m	3-pole "Wieland - gesis classic" type or compatible connector with 0.5m cable		

**note - price for uncommon RAL colour could be different from indicated. Ask before placing an order*

MPRZ LT92



Applications:

