


BETA LED

Floodlights



Images for the product family and options:



Description:

Surface mounted low-cost LED floodlight
Light distribution type: direct
Optical system: white thermoplastic reflector, symmetric, tempered glass diffuser,
Housing: die-cast aluminium
Colour: dark grey (RAL7043)

General data:

Mains voltage: 220-240V, 50-60Hz
LED lifetime, h: 25000/L70B50
SDCM: 6
Protection class IEC: I
Ingress protection code: IP65
Mechanical impact resistance: IK04
Operating temperature range, °C: ta -20...+40

Installation:

On the horizontal or vertical surface. Cable, 0.3m, 3x1.00mm²

Environment:

Outdoor

Application:

Facade illumination, parking area, park, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Beta LED1x2700 E923 T740	157	126	25	2700	30,0	90	70+	4000	0,40
Beta LED1x4500 E924 T740	208	170	36	4500	50,0	90	70+	4000	0,83
Beta LED1x9000 E925 T740	320	250	42	9000	100,0	90	70+	4000	1,83
Beta LED1x18000 E926 T740	418	334	43	18000	200,0	90	70+	4000	3,65

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

T740 Colour temperature 4000K, CRI 70+

Available accessories:



Product: Power supply connector - IP66/IP68, 3x1.5mm²
Description: Quick and easy to connect power supply and luminaire cable connector - IP66/IP68, 3x1.5mm², 400V/16A, 1pcs

STANDARD

